

TSC

The Smarter Choice.



ALPHA-2R – Portable Direct Thermal Printer

SMALLEST MOST AFFORDABLE MOBILE PRINTER



KEY FEATURES

- IP54-rated environmental case to resist the dust and water
- Plastic design construction that withstands 1.5 m (5 ft) drop
- Wired & wireless communication interfaces: USB 2.0, RS-232, Bluetooth 4.0, Bluetooth 4.2 + MFi, NFC and 802.11 a/b/g/n (supports either WiFi or Bluetooth)
- Wi-Fi Certified™
- High capacity 1620 mAh rechargeable Lithium Ion batteries
- Large paper capacity to reduce the frequency of changing paper roll
- High-speed processor and extensive memory for fast print speeds of up to 102 mm (4") per second
- Lasts more than 17 hours of printing receipts on a single battery charge
- Supports TSPL-EZ™ (EPL2 and ZPL emulations), ESC-POS, CPCL emulation
- 2-year standard warranty
- ENERGY STAR® qualified

APPLICATIONS

- Direct Store Deliveries (DSD)
- Proof of Delivery and Pickup
- Field Sales/Repairs
- Mobile Point-of-Sale
- Parking Citations
- Mobile Ticketing
- Onboard Transportation Ticketing
- Utility Billing/Meter Reading
- Fleet Management

ALPHA-2R – Portable Direct Thermal Printer

PRINTER MODEL	Alpha-2R
Resolution	8 dots/mm (203 DPI)
Printing method	Direct Thermal
Max. print speed	102 mm (4")/second
Max. print width	48 mm (1.89")
Max. print length	2,286 mm (90")
Enclosure	Plastic
Physical dimension	89.3 mm (W) x 134.5 mm (H) x 56.5 mm (D) 3.52" (W) x 5.3" (H) x 2.22" (D)
Weight (including battery)	0.35 kg (0.77 lbs)
Drop specification	1.5 m (5 ft), with IP54 case can be 2 m (6.5 ft)
IP rating	IP42 (without case) IP54 (with case)
Max. roll capacity	50 mm (2") OD
Processor	32-bit RISC CPU
Memory	<ul style="list-style-type: none"> • 128 MB Flash memory • 64 MB SDRAM
Interface	<ul style="list-style-type: none"> • USB 2.0 • 802.11 a/b/g/n wireless (factory option) • Bluetooth 4.0 (factory option) • Bluetooth 4.2 + MFi (factory option) • NFC (factory option) • RS-232 (user option)
Power	Two-cell, 7.4V DC, 1620 mAh Li-ion rechargeable battery
Operation switch, button	<ul style="list-style-type: none"> • 3 buttons (On/off, feed, and cover-open) • 2 color LED for printer status, 3 LEDs for battery status
Sensors	<ul style="list-style-type: none"> • Reflective sensor • Head open sensor
Internal fonts	<ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • One Monotype Imaging® CG Triumvirate Bold Condensed scalable font
Bar code	<ul style="list-style-type: none"> • 1D bar code Code 39, Code 93, Code128UCC, Code128 subsets A.B.C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 Data bar • 2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec
Printer language	TSPL-EZ™ (EPL2, ZPL2), ESC-POS or CPCL emulation
Media type	Receipt paper, bline receipt paper (mark in printing side) & selected label
Media width	Max 58 mm (2.28") *with adapter: 50.8 mm (2") and 25.4 mm (1") (user option)
Media thickness	Receipt: 0.05 ~ 0.10 mm (2 ~ 4 mil) Label: Fasson media up to 0.14 mm (5.5 mil)
Media height	Label: Min. 25.4 mm (1")
Environment condition	Operation: -20 ~ 50 °C (-4 ~ 122 °F), 10 ~ 90% non-condensing Storage: -30 ~ 70 °C (-22 ~ 158 °F), 10 ~ 90% non-condensing
Safety regulation	FCC, IC, CE, CB, CCC, SRRC, BC, TÜV, NCC, Energy Star®
Environmental concern	Comply with RoHS, WEEE, REACH
Accessories	<ul style="list-style-type: none"> • Quick start guide • Belt clip • Li-ion battery • Power adapter
Limited warranty	<ul style="list-style-type: none"> • Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first
Factory options	<ul style="list-style-type: none"> • 802.11 a/b/g/n wireless network (supports either WiFi or Bluetooth) • Bluetooth • MFi • Linerless • NFC • Fork truck mount, cart mount
User options	<ul style="list-style-type: none"> • Mini type USB 2.0 • USB to RS-232 converter cable • Li-ion battery • Charge station 1 cell (with changeable power connector) • Charge station 4 cell (with changeable power connector) • Vehicle power adapter • IP54-rated environmental case with shoulder strap • 12-24V DC automobile cigarette lighter plug • Adapters for 1" or 2" media roll width

* MFi will be available in January 2017



CORPORATE HEADQUARTERS

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

LI ZE PLANT

TSC Auto ID Technology Co., Ltd.
Tel: +886 3 990 6677
E-mail: apac_sales@tscprinters.com

AMERICAS

TSC Auto ID Technology America Inc.
Tel: +1 657 258 0808
E-mail: americas_sales@tscprinters.com

MEXICO

TSC Mexico Representative Office
Tel: +52 (33) 3165 7379
E-mail: americas_sales@tscprinters.com

BRAZIL

TSC Brazil Representative Office
Tel: +55 (11) 99597 8098
E-mail: americas_sales@tscprinters.com

EMEA

TSC Auto ID Technology EMEA GmbH
Tel: +49 (0) 8106 37979 00
E-mail: emea_sales@tscprinters.com

RUSSIA

TSC Auto ID Technology EMEA GmbH
Tel: +7 495 249 9017
E-mail: emea_sales@tscprinters.com

MIDDLE EAST

TSC Auto ID Technology ME Ltd, FZE
Tel: +971 4 2533 069
E-mail: emea_sales@tscprinters.com

ASIA PACIFIC

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd.
Tel: +86 22 5981 6661
E-mail: apac_sales@tscprinters.com



TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
© 2016 TSC Auto ID Technology Co., Ltd.
Product models and Specifications are subject to change without notice.
Contact your TSC sales representative for specific information.